## Claims

- [c0001] 1. A device for manually stuffing sausage comprising:

  horn means comprising a horn inlet and a horn outlet,

  piston means; said piston means adapted to pass at least

  within said horn means from said horn inlet to said horn

  outlet.
- [c0002] 2. The device of Claim 1 wherein said horn inlet and said horn outlet have substantially similar diameters and said piston means is capable of slidable movement therebetween.
- [c0003] 3. The device of Claim 1 wherein said horn outlet further comprises means for releasably securing a retaining collar thereto.
- [c0004] 4. The device of Claim 3 wherein said retaining collar is operatively arranged to secure a bell-shaped tube proximate said horn outlet, said bell-shaped tube comprising a tube inlet and a tube outlet, said tube inlet having a diameter substantially similar to said horn outlet.
- [c0005] 5. The device of Claim 1 further comprising a two-part handle and means for releasably pivotally securing said two part handle to said horn means.

- [c0006] 6. The device of Claim 5 wherein a first part and a second part of said two part handle are adapted for releasable complementary mate with one another such that said first part may be locked to said second part.
- [c0007] 7. The device of Claim 6 wherein said first part comprises means for releasably pivotally securing said handle to said horn means and means for releasably pivotally securing a piston means thereto.
- [c0008] 8. The device of Claim 7 wherein said piston means is capable of slidable movement within said horn means and between said horn inlet and said horn outlet.
- [c0009] 9. The device of Claim 1 further comprising mounting means for elevating said horn above a work surface.
- [c0010] 10. The device of Claim 1 wherein said horn means is arcuate.
- [c0011] 11. A device for manually stuffing sausage comprising: arcuate horn means comprising a horn inlet and a horn outlet, piston means, said piston means adapted to pass at least within said horn means from said horn inlet to said horn outlet; a retaining collar; and,

a bell-shaped tube, said retaining collar adapted to be releasably secured to said horn outlet, said retaining collar operatively arranged to secure said bell-shaped tube proximate said horn outlet, said bell-shaped tube comprising a tube inlet and a tube outlet, said tube inlet having a diameter substantially similar to said horn outlet.

- [c0012] 12. The device of Claim 11 further comprising a twopart handle and means for releasably pivotally securing said two part handle to said arcuate horn means.
- [c0013] 13. The device of Claim 12 wherein a first part and a second part of said two part handle are adapted for releasable complementary mate with one another such that said first part may be locked to said second part.
- [c0014] 14. The device of Claim 13 wherein said first part comprises means for releasably pivotally securing said handle to said arcuate horn means and means for releasably pivotally securing said piston means.
- [c0015] 15. The device of Claim 14 wherein said piston means is arranged for slidable movement along the entire length of said arcuate horn means.
- [c0016] 16. The device of Claim 15 further comprising mounting means for elevating said arcuate horn above a work sur-

face.

- [c0017] 17. The device of Claim 11 wherein said horn inlet has a diameter substantially equal to that of said horn outlet.
- [c0018] 18. A device for manually stuffing sausage comprising: horn means comprising a horn inlet and a horn outlet; handle means comprising a piston means, said piston means adapted to pass at least within said horn means from said horn inlet to said horn outlet; a retaining collar; and,
  - a bell-shaped tube, said retaining collar adapted to be releasably secured to said horn outlet, said retaining collar operatively arranged to secure said bell-shaped tube proximate said horn outlet, said bell-shaped tube comprising a tube inlet and a tube outlet, said tube inlet having a diameter substantially similar to said horn outlet.